

➤ HIGH CURRENT CONNECTOR FOR OUTSIDE USE

This connector is designed for high current applications up to 65 A. It can be used for outboard engines, wind generators, solar panels, hydro generators or electric propulsions. The internal clip mechanism allows an easy connection: insert the dismantled cable, close the clip and fasten the

housing - that's it!

The connector is watertight protection IP 68 while connected. The locking mechanism avoids unintended disconnection of the connector.

PC 65 Set	Order-No.: 6 2179 0900
Cross sections	6- 16 mm ² .
Voltage	max. 1500 V DC
Current	max. 65 A DC
Protection	IP 68
Dimensions while connected	L 120 x Ø 35 mm.



A set consists of a coupling plug and a coupling socket for plus and negative. They are colour coded.

➤ USB-CHARGING SOCKETS

NEW



USD FM Order-No.: 7 0030 0240

USB double charging socket DC 12/24 V, output USB: 5 V, 2 x 1,5 A. Fitting hole Ø 30 mm, front fitting version. Ø 47 mm, depth only 23 mm !

NEW



USD GW Order-No.: 7 0030 0250

USB double charging socket DC 12/24 V, output USB: 5 V, 2 x 1,5 A. Fitting hole Ø 30 mm, fastening by a hex nut Ø 37, depth only 23 mm !

NEW



USD EK Order-No.: 7 0010 1039

USB double charging socket incl. cap, DC 12 / 24 V, output USB: 5 V 2x 2,5 A, max 4.8 A. Cut-out: 37 x 21,5 mm, depth 60 mm. For use with panels series STV 700.

NEW



USF 3A Order-No.: 3 6733 9000

Flat USB built on socket 12/24VDC
Output USB: 5 V, 3 A.
Dimensions L 42 x W 34 x H 15 mm

UWB Order-No.: 3 6730 2100

Angle adjustable USB-double charging socket DC 12/24 V, output 5 V (2 x 2,5 A).
For the use with cigarette lighter or standard socket outlets.

USV Order-No.: 7 0010 1044

USB -data inlet incl. cap and USB extension-cable, length 1,5 m.
Fitting hole Ø 29 mm, suits USB 2.0.

NEW



USD 5D Order-No.: 3 6732 1100

USB double charging socket DC 12/24 V. Output USB: 5 V, 2 x 2,5 A. Fitting hole Ø 28 mm, depth 60 mm, fastening by a hex nut.

USB 3 Order-No.: 3 6733 1000

as above, 1xUSB-output 5 V, 3 A, without cap

USD 5D MP Order-No.: 3 6732 2100

USB double charging socket DC 12/24 V with assembly plate 60 x 40 mm. Output USB: 5 V, 2 x 2,5 A. Fitting hole Ø 28 mm, depth 60 mm.

USB 3 MP Order-No.: 3 6733 2000

as above, 1xUSB-output 5 V, 3 A, without cap

USD 12/24 A Order-No.: 3 6732 3000

Double USB built on socket DC 12/24 V / Output USB: 5 V, 2 x 2,5 A. No cap.

Dimensions L 85 x W 34 x H 33 mm

USB 3 A Order-No.: 3 6733 3000

as above, 1xUSB-output 5 V, 3 A, without cap