



CABLES AND CAPS



- BA 1 rt Order-No.: 7 0010 4010
- BA 1 sw Order-No.: 7 0010 4011

Cable cap insulators. Insulates single studs.
For cable cross section 10 – 25 mm²



- BA 2 rt Order-No.: 7 0010 4012
- BA 2 sw Order-No.: 7 0010 4013

Cable cap insulators. Insulates single studs.
For cable cross section 35 – 70 mm²



- BA 3 rt Order-No.: 7 0010 4014
- BA 3 sw Order-No.: 7 0010 4015

Cable cap insulators. Insulates single studs.
For cable cross section 95 – 120 mm²



Multicore flexible cable for DC or mast installation.

Can be used in dry, humid or wet places, isolation grey PVC. Temperature range -40...+80 °C. Non combustible, nominal voltage 300 V.

- OB 2 x 1,5 mm², Ø 6,6 mm Order-No.: 5 0001 1077
- OB 4 x 1,5 mm², Ø 7,8 mm Order-No.: 5 0001 1081
- OB 2 x 2,5 mm², Ø 7,9 mm Order-No.: 5 0001 1104
- OZ 4 x 2,5 mm², Ø 9,8 mm Order-No.: 5 0001 1108
- OB 2 x 4 mm², Ø 9,2 mm Order-No.: 5 0001 1121



Tinned multicore flexible cable for DC or mast installation.

Can be used in dry, humid or wet places. Isolation black PVC. Temperature range -40...+80 °C. Non combustible, nominal voltage 300 V.

- H05VV-VZ 2 x 1,5 mm², Ø 8 mm Order-No.: 5 0338 8215
- H05VV-VZ 2 x 2,5 mm², Ø 9 mm Order-No.: 5 0338 8225



Multicore flexible cable for AC 230 V installation.

Can be used in dry, humid and wet areas, but only for inside installation. Isolation grey PVC. Temperature range -40...+80 °C. Non combustible, nominal voltage 300 V.

- JB 3 x 1,5 mm², Ø 7,0 mm Order-No.: 5 0001 1078
- JB 3 x 2,5 mm², Ø 8,8 mm Order-No.: 5 0001 1105



Tinned multicore flexible cable for AC 230 V installation.

Can be used in dry, humid and wet areas, also outside, weatherproof. Isolation made by EPR/PUR - yellow, oil and acid resistant. Temperature range -40...+80 °C, non combustible, nominal voltage 450 V.

- H07BQ-F 3 x 1,5 mm², Ø 9,5 mm Order-No.: 7 0050 1530
- H07BQ-F 3 x 2,5 mm², Ø 10,5 mm Order-No.: 7 0050 2530
- H07BQ-F 3 x 4 mm², Ø 13 mm Order-No.: 7 0051 4030
- H07BQ-F 3 x 6 mm², Ø 14 mm Order-No.: 7 0051 6030



Shore power cable 230 V / 16 A. for the use outside, weatherproof. Isolation black neoprene 3 lines, non combustible, temperature range -30...+60 °C, nominal voltage 450 V.

- H07RN-F 3 x 2,5 mm², Ø 13,0 mm Order-No.: 5 0730 2530



Tinned Shore power cable 230 V / 16 A. for the use outside, weatherproof. Isolation EPR/PUR - yellow, oil and acid resistant, temperature range -40...+80 °C, non combustible, nominal voltage 450 V.

- H07BQ-F 3 x 2,5 mm², Ø 10,5 mm Order-No.: 7 0050 2530



Multicore flexible control cable (without shield) and data cable (shielded)
Can be used in dry, humid and wet areas, but only for inside installation. Isolation grey PVC. Temperature range -40...+80 °C. Non combustible, self extinguishing.



- LIYY 3 x 0,34 mm², Ø 4,5 mm Order-No.: 5 0001 8058
- LIYY-CY 3 x 0,5 mm², shielded Ø 6,8 mm Order-No.: 5 0002 0057
- LIYY-CY 6 x 0,5 mm², shielded, Ø 7,3 mm Order-No.: 5 0001 6005
- LIYY 8 x 0,5 mm², Ø 7,8 mm Order-No.: 5 0001 8091