

➤ BATTERIES

EXIDE DUAL AGM batteries are high current batteries and have been designed to supply the DC system with energy as well as to deliver high power current for a good engine starting.



- Maintenance free
- Suitable for long breaks at 0 A consumption
- Without space restrictions
- Safe and clean (leak proof)
- High vibration resistance & tipping possibility
- Up to 50 % shorter charge time

EXIDE-AGM Type	Order-No.:	Voltage V	Capacity K20 (Ah)	CCA (A)	Dimensions			Weight kg
					L	W	H	
■ EK 920	6 1874 9900	12	92	860	353	175	190	27
■ EP 1200	6 0132 0140	12	140	700	513	189	223	45
■ EP 1500	6 0132 0180	12	180	900	513	223	223	55
■ EP 2100	6 0132 0240	12	240	1200	518	279	240	72

➤ 2V GEL BATTERIES (OPZV)



The gel batteries in 2V technology (OPzV) is the professional solution for big battery-capacities in order to avoid the parallel connection of small batteries. The possibility to check the voltage of each cell at any time offers a quick check during the lifetime. The construction in tube plate technology (armour plate-battery) ensures a very long lifespan even under rough conditions as vibration and shock.

Delivery incl. cell connectors.

- **Outstanding cycle quality**
2400 cycles at 60% disch. level (C₁₀) and 20 °C
- **Absolutely maintenance free battery**
acc. DIN 40742
- **Deep discharge safe**
acc. DIN 43 539 T5
- **Low self discharge**
Storage life up to 1 year at +30 °C
- **Installation also in horizontal position**
easy installation and maintenance
- **Approvals**
Germanischer Lloyd (GL), (UL), DIN/Gost/TÜV

2V-GEL Type	Type acc DIN 40742	Order-No.	Voltage V	Capacity K10 (Ah)	Dimensions			Height incl. terminals	Weight kg	Connection	Pole layout (see data sheet)
					L	W	H				
■ A 602/335	6 OPzV 300	6 0131 0300	2	337	147	208	357	399	27.0	F-M8	1
■ A 602/415	5 OPzV 350	6 0131 0350	2	416	126	208	473	515	30.0	F-M8	1
■ A 602/500	6 OPzV 420	6 0131 0420	2	499	147	208	473	515	35.0	F-M8	1
■ A 602/580	7 OPzV 490	6 0131 0490	2	582	168	208	473	515	39.0	F-M8	1
■ A 602/750	6 OPzV 600	6 0131 0600	2	748	147	208	648	690	49.0	F-M8	1
■ A 602/1010	8 OPzV 800	6 0131 0800	2	998	212	193	648	690	66.0	F-M8	2

■ **BA 5** Order-No.: 7 0010 4005

Cover for battery poles type BK 6 and BKM for cable cross section from 25 up to 50 mm².
Delivery as pair red/black.

■ **BA 7** Order-No.: 7 0010 4006

Cover for battery poles type BK 6 and BKM for cable cross section up to 95 mm².
Delivery as pair red/black.

■ **BA 6** Order-No.: 6 0140 4568

Single black cover for battery poles type BK 6 and BKM